

Recycled Mailer/Parcel Film

Recycled mailer film is specifically engineered for ecommerce order fulfillment applications. The co-extruded film contains a unique blend of resins, plus at least 25% recycled content.

The white opaque, matte exterior finish provides security and is ideal for both direct thermal transfer imprinting and adhesive label applications.

USER BENEFITS

- At least 25% pre-consumer recycled content
- Recyclable anywhere plastic bags are accepted
- Superior strength and reinforced side seals

TYPICAL APPLICATIONS

- Soft Goods Fulfillment
- Pharmacy Fulfillment
- Industrial Fulfillment
- Novelty Fulfillment
- Catalog Order Fulfillment

TECHNICAL SPECIFICATIONS

Compliances: N/A

Press Printing: Yes with restrictions

Imprinting: Yes

Trim Seal: Yes

Mil Thickness: 2.0, 2.5, 3.0



| Performance Data | U/M | 2.0 mil | 2.5 mil | 3.0 mil | ASTM |
|----------------------------|----------------------------|---------|---------|---------|--------|
| Haze | % | Opaque | Opaque | Opaque | D-1003 |
| Puncture Resistance (Dart) | grams | 249 | 292 | 396 | D-1709 |
| Tensile Strength MD | psi | 4246 | 4450 | 4930 | D-882A |
| Tensile Strength TD | psi | 4085 | 4315 | 4479 | D-882A |
| Elongation MD | % | 578 | 620 | 673 | D-882A |
| Elongation TD | % | 647 | 679 | 690 | D-882A |
| Elemendorf Tear MD | grams | 678 | 1063 | 1361 | D-1922 |
| Elemendorf Tear TD | grams | 1360 | 1678 | 2100 | D-1922 |
| OTR | cc/100in ² /day | N/A | N/A | N/A | D-3985 |
| MVTR | cc/100in ² /day | N/A | N/A | N/A | F-1249 |



Due to the recycled content of the material, the physical properties of this film are subject to vary beyond the typical expectations of virgin film. This data should be used for reference purposes only. Certain minimum purchase volumes may apply.